



Technical Data Sheet

Reflections 8mm Evoke





General

Size	1215mm x 195mm	
Thickness	8mm	

Commercial & Residential Applications

Pack Coverage	1.8954m²
Pack Weight	13kg
Planks per Box	8
Colours	9
Surface Finish	Embossed in Register
Profile	4 Sides Micro Bevel
Click System	Uniclic
Top Layer	Wood Paper with Aluminium Oxide
Core	910kg/m ³ High Density Fibreboard
Back Layer	Wood Paper with Aluminium Oxide
Maintenance	As per Australian Select Timbers timber flooring care & maintenance instructions - please refer to: asttimbers.com.au/technical/care-maintenance/



Technical Data Sheet

Reflections 8mm Evoke

Installation

Fully Bonded	No
Nailed	No
Floated on underlay	Yes*
Over heated slab	Yes*

^{*} Please refer to our Installation Instructions and Heated Slab Instructions for more information.

Test Results & Warranties

Acoustic Result*	Ln w = 53
Slip Testing	AS/NZS 4586-2013 Result:
	0.52, Classification: D1
Australian Reaction to fire - FLOOR	ASISO 9239.1-2003 Result CRF 7.1 kw/m², smoke value 10%
Release of formaldehyde	ASTM D5116 Result 0.054mg/ m ² /hr (max allowable 0.1)
Total VOC	ASTM D5116 Result 0.024mg/ m ² /hr (max allowable 0.5)
Abrasion Rating	AC4 Commercial Grade
Warranty - Domestic	25 Year
Warranty - Commercial	3 Year

^{*} All testing conducted on 200mm thick concrete slab with a 3mm Select EVA underlay using floated installation method and with 35mm furring channels and a single layer of 10mm standard plasterboard ceiling as per B.C.A requirements. Please contact Australian Select Timbers for further information regarding this test result.

Installation & Warranty

All Reflection Laminate floors must be installed by a competent approved installer who will have the necessary skills and take individual site circumstance into account. Reflection Laminate floors warranty will only apply to floors which have been installed according to the Reflection Laminate floors installation instructions available in each box of Reflection Laminate floors.

25 year Residentia Warranty 3 year Commercial Warranty

Terms & Conditions: Please note this technical sheet was written by Australian Select Timbers Pty Ltd, All the information is specified correctly while writing and publication of the sheet. The company reserves the right to change the specifications of this product at any time without piror notice to third parties.