



Technical Data Sheet

Nouvelle Hybrid Range



General

Size (Oak)	1830mm x 229mm
Size (Aust)	1830mm x 180mm
Thickness	5.5mm

Commercial & Residential Applications

Pack Coverage (Oak)	2.5144m²
Pack Coverage (Aust)	1.9764m²
Pack Weight (Oak)	20kg
Pack Weight (Aust)	18kg
Planks per Box	6
Colours	10
Surface Finish	Embossed Matte Finish
Profile	4 Sides Micro Bevel
Click System	Drop Loc
Wear Layer	0.55mm
Core	Rigid Limestone Composite
Back Layer	1.5mm Cork
Maintenance	As per Australian Select Timbers timber flooring care & maintenance instructions - please refer to: asttimbers.com.au/technical/care-maintenance/





Technical Data Sheet

Nouvelle Hybrid Range

Installation

Fully Bonded	No
Nailed	No
Floated on underlay	Yes*
Over heated slab	Yes*

^{*} Please refer to our Installation Instructions and Heated Slab Instructions for more information.

Test Results & Warranties

Acoustic Result*	L'nt,w = 50
Slip Testing	AS/NZS 4586-2013 Result: Dry: 0.59, Classification: D0 Wet: 41, Classification: P3 Oil: 10°, Classification: R10
Australian Reaction to fire - FLOOR	ASISO 9239.1-2003 Result CRF 10.8 kw/m², smoke value 77%
Release of formaldehyde	0.008 mg/m2/hr (Green Star Standard: 0.1mg/m2/hr)
Total VOC	ASTM D5116 Result 0.020mg/ m²/hr (max allowable 0.5)
Warranty - Domestic	Life
Warranty - Commercial	15 Year

- * No further underlayment required for installation.
- * Please refer to our Nouvelle Hybrid Flooring Installation Instruction and Heated Slab instructions for more information.
- * Test certificates are available upon request.
- * Terms and conditions apply, please contact us for more information.

Installation & Warranty

All Nouvelle Hybrid floors must be installed by a competent approved installer who will have the necessary skills and take individual site circumstance into account. Nouvelle Hybrid floors warranty will only apply to floors which have been installed according to the Nouvelle Hybrid floors installation instructions available in each box of Nouvelle Hybrid floors.





Terms & Conditions: Please note this technical sheet was written by Australian Select Timbers Pty Ltd, All the information is specified correctly while writing and publication of the sheet. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.