

## De Marque Collection, Herringbone Engineered Oak 120 x 600 x 15/4 mm.

The stunning new De Marque Herringbone Collection is now available with a Universal Tongue & Groove profile that enables multiple pattern assembly to create a number of different visuals. With a contemporary palette of pre-finished colours, the range will provide warmth and charm to almost any interior. Also available in Raw (un-coated) for custom on-site finishing.

The Oak planks are manufactured from sustainable Real Oak timber combining a 4 mm solid Oak wear layer engineered onto an 11 mm plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of 15mm. It's perfectly suited for residential, multi-residential and commercial applications.

| De Marque Herringbone Collection |             |           | 120 x 600 x 15/4 mm |             |
|----------------------------------|-------------|-----------|---------------------|-------------|
| Colour                           | Scotia      | Trim      | Sqm/Ctn             | Micro Bevel |
| Ash Grey                         | Capital     | Walnut    | 0.72m2              | Yes 4 sides |
| Cognac                           | Rosybrown   | Oak       | 0.72m2              | Yes 4 sides |
| Raw ( Un-coated)                 |             |           | 0.72m2              | Yes 4 Sides |
| Sauvignon                        | Limewash    | Champagne | 0.72m2              | Yes 4 sides |
| Vintage                          | Spotted Gum | Champagne | 0.72m2              | Yes 4 sides |

**Parquetry Installation:** we recommend a full trowel spread adhesive bonded to a homogenous, flat and dry surface such as plywood. Wooden tongue inserts are provided to aid pattern design and assembly. **Parquetry is not suitable as a floating installation. For concrete slabs,** the slab must be dry <2.2% with full Moisture Barrier applied. The parquetry is then adhered with a matching brand elastomeric wood floor adhesive. Sika brand products are recommended.

**Key Features;** Engineered to exacting standards. Manufactured from environmentally sustainable resource. A permanent and solid fixture to your floor. Extremely stable with excellent wear resistance. Wear layer can be refurbished when required.

**Description;** Engineered Oak, Universal Tongue & Groove (1 side Tongue / 3 side Groove)

**Grade & Surface;** A/B/C/D Grade contains knots and split defects that are filled to compliment surface character. Pre-finished, PU Matte coating. Light wire brush surface texture.

**Size & Length;** 120mm, width, 600mm, length, 15mm, thickness. 4 mm, Oak Wear Layer.

**Profile;** Universal T&G for multiple pattern assembly, (wooden tongue inserts supplied). **Micro Bevelled Edges**

**Slip Resistance;** in accordance with AS/NZS 4586 2013 P3. **VOC Emissions;** < E1, (Below World Health Organisation Levels)

**Fire Test Data;** Test Method AS/ISO9239.1. Critical Radiant Flux, 5.6kW/m2 Mean Smoke Development, 6 percent minutes



For specification or reseller support contact, [www.preferencefloors.com.au](http://www.preferencefloors.com.au)

### Preference Floors (SA)

ABN 63 600 454 215

47 Research Road,  
Pooraka SA 5095

t +61 8 82622774

f +61 8 8268 8919

e [sa@preferencefloors.com.au](mailto:sa@preferencefloors.com.au)

### Preference Floors (QLD)

ABN 81 169 158 990

6/268 Evans Road,  
Salisbury QLD 4107

t +61 7 3875 1688

f +61 7 3875 1788

e [qld@preferencefloors.com.au](mailto:qld@preferencefloors.com.au)

### Preference Floors (VIC)

ABN 34 151 422 927

19 Lanyon Street,  
Dandenong South VIC 3175

t +61 3 9794 5111

f +61 3 9794 5133

e [vic@preferencefloors.com.au](mailto:vic@preferencefloors.com.au)

### Preference Floors (NSW)

ABN 40 117 801 037

Unit A/31 Sturt Street,  
Smithfield NSW 2164

t +61 2 9738 1188

f +61 2 9738 1199

e [sales@preferencefloors.com.au](mailto:sales@preferencefloors.com.au)